

DWL 215

TAKTON



Benefits:

- Up to 50% energy savings compared with TL-D
- Reliable LED technology – maintenance-free
- Direct replacement for conventional waterproof and wall mounted luminaires in terms of light performance
- Universal solution covering various application requirements



FAMILY INFORMATION

Type

DWL 215

Light source

LED module

Driver

Driver included

Input voltage

220 – 240 V

Power factor

0,93

Power consumption

7-14 W

Initial luminous flux

700 – 1500 lm depending on type

Initial LED luminaire efficacy

90 – 100 lm/W depending on type

Light color

Neutral White – 4000 K

Color rendering index (CRI)

>80

Maintenance of lumen output - L80B20

30000 hours

Optical cover

Injection molded polycarbonate (PC)

Body material

Flame retardant glass-fibre reinforced polyester

Color

Light grey

Impact resistance

IK10 as option

Ingress protection

IP65, IP66 as option

Electrical safety

Class II

Application

Parking garages • Basements • Cellars • Warehouses • General lighting

DWL 215

TAKTON

PRODUCT FAMILY RANGE

Code	Type	Power onsupption W	Initial luminous flux lm	Color K	Diffuser	Ingress Protection
700151252800	DWL215 LED007 7W I 830 IP65 IK08 PC OPAL	7	700	3000	PC opal	IP65
700151252801	DWL215 LED007 7W I 840 IP65 IK08 PC OPAL	7	700	4000	PC opal	IP65
700151252802	DWL215 LED007 7W I 830 IP65 IK08 PC OPAL MS	7	700	3000	PC opal	IP65
700151252803	DWL215 LED007 7W I 840 IP65 IK08 PC OPAL MS	7	700	4000	PC opal	IP65
700151252804	DWL215 LED009 9W I 830 IP65 IK08 PC OPAL	9	900	3000	PC opal	IP65
700151252805	DWL215 LED009 9W I 840 IP65 IK08 PC OPAL	9	900	4000	PC opal	IP65
700151252806	DWL215 LED009 9W I 830 IP65 IK08 PC OPAL MS	9	900	3000	PC opal	IP65
700151252807	DWL215 LED009 9W I 840 IP65 IK08 PC OPAL MS	9	900	4000	PC opal	IP65
700151252808	DWL215 LED015 14W I 830 IP65 IK08 PC OPAL	14	1500	3000	PC opal	IP65
700151252809	DWL215 LED015 14W I 840 IP65 IK08 PC OPAL	14	1500	4000	PC opal	IP65
700151252810	DWL215 LED015 14W I 830 IP65 IK08 PC OPAL MS	14	1500	3000	PC opal	IP65
700151252811	DWL215 LED015 14W I 840 IP65 IK08 PC OPAL MS	14	1500	4000	PC opal	IP65